

Data Sheet

BIZERBA

iL Professional 800F/MP

Load receptor iL Professional 800F/MP impresses due to its simple but robust design. Due to its flexible use whether floor mount or pit mount it shows its true strength up to a load capacity of 800 kg.



More information
High performance
with a wide range of
solutions and options.

Product description

The iL Professional 800F/MP carries out demanding and precise applications. This sophisticated load receptor is, besides the standard resolution of 3,000e, also suitable for higher requirements such as 2x3,000e as dual interval but also for 6,000e. Due to its flat design it can be perfectly integrated in different systems. Available in painted steel or stainless steel the iL Professional 800F/MP covers a broad spectrum.

Even for applications in hazardous areas there are no restrictions for this load receptor. By means of load cells suitable for zones 2/22 and 1/21 it shows its strength.



iL Professional 800F/MP

Highlights

- Dimensions from 800 x 600 mm up to 1,000 x 800 mm
- Painted steel version or entirely made of stainless steel
- Minimal overall height of 81 mm
- Floor mount or pit mount with pit frame
- Weighing ranges from 30 kg to 600 kg, with intervals from 10 g to 100 g
- Resolution 3,000e, 2 x 3,000e as dual interval or 6,000e
- Variants for Ex zones 2/22 and 1/21
- IP65 protection

Options

- Pit frame made of painted steel or stainless steel
- Pit support plates if pit already exists
- Intrinsically safe version suitable for zones 1/21 and 2/22

My Bizerba

We offer you solutions from a single source which can be customized and allow you to respond to any change in a flexible manner. Benefit from costs which can be planned and efficient processes. We are happy to advise you.

Bizerba SE & Co. KG
Wilhelm-Kraut-Straße 65
72336 Balingen

T +49 7433 12-0
fax: +49 7433 12-2696
marketing@bizerba.com

www.bizerba.com